

# **Material Safety Data Sheet**

Revision Date: 28-Apr-2014 Revision Number: 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name BENJAMIN MOORE ACRYLIC KNOCKDOWN FLAT

Product Code 343

Product Class WATER THINNED PAINT

**Color** White

Manufacturer Emergency Telephone Number(s)

Benjamin Moore & Co. CHEMTREC: 800-424-9300

101 Paragon Drive Montvale, NJ 07645 Phone: 855-724-6802 www.benjaminmoore.com

## 2. COMPOSITION INFORMATION ON COMPONENTS

**Hazardous Components** 

1424146466611161116		
Chemical Name	CAS-No	Weight % (max)
Limestone	1317-65-3	30
Silica, crystalline	14808-60-7	15
Silica, mica	12001-26-2	10
Titanium dioxide	13463-67-7	5
Kaolin	1332-58-7	5
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	0.5

## 3. HAZARDS IDENTIFICATION

## **Emergency Overview**

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis.

Appearance liquid Odor little or no odor

**Potential Health Effects** 

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Effects** 

**Eyes** May cause slight irritation.

**Skin** Substance may cause slight skin irritation.

343 - BENJAMIN MOORE ACRYLIC KNOCKDOWN FLAT

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Chronic Effects** Repeated contact may cause allergic reactions in very susceptible persons.

Contains: Crystalline Silica which has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of

Revision Date: 28-Apr-2014

inhalation exposure to spray mist or dust from sanding the dried paint.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions None known

HMIS Health: 1\* Flammability: 0 Reactivity: 0 PPE: -

### **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special"

handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

## 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact**Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician if

necessary.

Notes To Physician Treat symptomatically

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

343 - BENJAMIN MOORE ACRYLIC KNOCKDOWN FLAT

Protective Equipment And Precautions For Firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 28-Apr-2014

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or extreme

heat.

No

Sensitivity To Mechanical Impact No **Sensitivity To Static Discharge** 

Flash Point Data

Flash Point (°F) Not applicable Flash Point (°C) Not applicable **Flash Point Method** Not applicable

Flammability Limits In Air

**Lower Explosion Limit** Not applicable **Upper Explosion Limit** Not applicable

**NFPA** Health: 1 Flammability: 0 Instability: 0 Special: Not Applicable

### NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Environmental Precautions** Prevent further leakage or spillage if safe to do so.

**Methods For Clean-Up** Soak up with inert absorbent material. Sweep up and shovel into suitable containers

for disposal.

Other Information None known

## **HANDLING AND STORAGE**

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

#### 8. **EXPOSURE CONTROLS / PERSONAL PROTECTION**

## **Exposure Limits**

**Hazardous Components** 

\_\_\_\_

Revision Date: 28-Apr-2014

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
	A2 - Suspected	1 - Human	Known Human	Listed
Silica, crystalline	Human	Carcinogen	Carcinogen	
	Carcinogen		_	
		2B - Possible		Listed
Titanium dioxide		Human		
		Carcinogen		
		1 - Human		
Distillates (petroleum), solvent-dewaxed heavy paraffinic		Carcinogen		

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

## **Product**

**Acute Toxicity to Fish** 

No information available

## **Acute Toxicity to Aquatic Invertebrates**

No information available

## **Acute Toxicity to Aquatic Plants**

No information available

## Component

**Acute Toxicity to Fish** 

Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

## **Acute Toxicity to Aquatic Invertebrates**

No information available

## **Acute Toxicity to Aquatic Plants**

No information available

13. DISPOSAL CONSIDERATIONS
Waste Disposal MethodDispose of in accordance with federal, state, and local regulations. Dry, emptycontainers may be recyc
14. TRANSPORT INFORMATIONDOTNot regulatedICAO / IATANot i
15. REGULATORY INFORMATIONInternational Inventories
United States TSCAYes - All components are listed or exempt.Canada DSLNo - Not all of the components are listed.One or m
Federal Regulations
SARA 311/312 hazardous categorization Bhottliffide Hotelstate Attantal MeSARA 313  NeSARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains achemical
This product contains the following HAPs:
State Regulations

## **California Proposition 65**

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

## State Right-to-Know

<b>Chemical Name</b>	Massachusetts	New Jersey	Pennsylvania	Louisiana	Rhode Island
Limestone	X	Χ	X		X
Silica, crv					